

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Page 1/9

MCCH

Reviewed on 03/22/2024

1 Identification

- · Product identifier
- Trade name: Medium Cure Ceramic Epoxy
 Relevant identified uses of the substance or mixture and uses advised against
 No further relevant information available.
 Description Description Description
- Product description Permanent Thermal Adhesive
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Arctic Silver Incorporated 9826 West Legacy Ave. Visalia, CA 93291 USA Voice: 559.740.0912 Fax: 559.740.0913 infoas@arcticsilver.com www.arcticsilver.com
- *Emergency telephone number:* Rocky Mountain Poison Control Toll Free: 877-740-5015 Alternate: 303-739-1110

2 Hazard(s) identification

· Classification of the substance or mixture



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

- Hazard-determining components of labeling: Epoxy resin Aluminum Oxide Boron Nitride
 Hazard statements
- Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation.
- · Precautionary statements

Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves.

Arctic Silver

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Trade name: Medium Cure Ceramic Epoxy

Wear eye protection / face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eve irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container in accordance with local/regional/national/international regulations. · Unknown acute toxicity: 48 percent of the mixture consists of ingredient(s) of unknown toxicity. · Classification system:

• NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



· Hazard(s) not otherwise classified (HNOC): None known

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous	Components:
-------------	-------------

CAS: 25068-38-6	Epoxy resin	45-60%
	Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	
CAS: 1344-28-1	Aluminum Oxide	20-35%
RTECS: BD 1200000	♦ STOT SE 3, H335	
CAS: 10043-11-5	Boron Nitride	15-25%
	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320	

4 First-aid measures

· Description of first aid measures

· After inhalation:

Consult a doctor for complaints.

In case of unconsciousness, place patient securely on side position for transportation.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Trade name: Medium Cure Ceramic Epoxy

- *After skin contact:* Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.
- · After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor. Have eyes examined and tested by medical personnel.

· After swallowing:

Seek immediate medical advice.

Never give anything by mouth to an unconscious person.

- Do not induce vomiting.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use firefighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

KEEP OUT OF REACH OF CHILDREN! Avoid prolonged or repeated skin contact. Avoid breathing vapors. Do not incinerate or burn containers. Always replace overcap when not in use. Avoid use around open flames and other sources of ignition. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Ensure that all equipment is grounded to prevent static discharge. Containers of this material may be hazardous when emptied due to solid or vapor residue. Wash hands after use. Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Trade name: Medium Cure Ceramic Epoxy

- · Specific end use(s) No further relevant information available.
- 8 Exposure controls/personal protection
- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with occupational exposure limits:
- 25068-38-6 Epoxy resin
- PEL
 Short-term value: 5 mg/m³

 Long-term value: 15 mg/m³

 STEL
 Short-term value: 5 mg/m³

 Long-term value: 10 mg/m³

 TLV
 Long-term value: 10 mg/m³

• Additional information: The lists that were valid during the creation of this SDS were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/

the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Arctic Silver

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Trade name: Medium Cure Ceramic Epoxy

9 Physical and chemical properties		
Information on basic physical and	chemical properties	
General Information		
· Appearance: Form:	Viscous	
Color:	White	
· Odor:	A: Slight epoxy odor	
	B: Mercaptan sulfur odor	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	2980 °C (5396 °F)	
· Flash point:	> 204 °C (> 399 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not self-igniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure:	<0.15 mmHg	
Density @ 20 °C (68 °F):	1.6-1.8 g/cm³ (13.352-15.02 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	ter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	0.0 %	
• Other information	No further relevant information available.	

· *Reactivity* No further relevant information available.

· Chemical stability Stable under normal conditions.

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, flame and ignition sources.

· Incompatible materials: Strong oxidizing agents, strong reducing agents



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Page 6/9

Trade name: Medium Cure Ceramic Epoxy

· Hazardous decomposition products:

Fumes produced when heated to decomposition may contain carbon monoxide, carbon dioxide, ammonia, and aldehydes.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:
- 25068-38-6 Epoxy resin
- Oral LD50 >2000 mg/kg (rat)

Dermal LD50 >2000 mg/kg (rat)

- · Primary irritant effect:
- on the skin:
- Irritant to skin and mucous membranes.
- · on the eye:
- Irritating effect.
- Causes serious eye irritation.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- *IARC (International Agency for Research on Cancer)* None of the ingredients are listed.
- NTP (National Toxicology Program)

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:	
25068-38-6 Epoxy resin	
EC50 3.6 mg/l (daphnia)	

· Persistence and degradability No further relevant information available.

- · Behavior in environmental systems:
- · *Bioaccumulative potential* No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Trade name: Medium Cure Ceramic Epoxy

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14 Transport infor	mation
--------------------	--------

· UN-Number				
· DOT, ADR, ADN, IMDG, IATA	Non-Regulated Material			
· UN proper shipping name	-			
· DOT, ADR, ADN, IMDG, IATA	Non-Regulated Material			
 Transport hazard class(es) 				
· DOT, ADR, ADN, IMDG, IATA				
· Class	Non-Regulated Material			
· Packing group	5			
· DOT, ADR, IMDG, IATA	Non-Regulated Material			
Environmental hazards:	Not applicable.			
 Special precautions for user 	Not applicable.			
Transport in bulk according to Annex II of				
MARPOL73/78 and the IBC Code	Not applicable.			
• UN "Model Regulation":	-			
15 Regulatory information				

- Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients are listed.

- Section 313 (Specific toxic chemical listings):
 1344-28-1 Aluminum Oxide
- · TSCA (Toxic Substances Control Act):

All ingredients are listed.

· California Proposition 65

Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

(Contd. on page 8)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Page 8/9

I (oral)

A4

Trade name: Medium Cure Ceramic Epoxy

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)
- 10043-11-5 Boron Nitride
- TLV (Threshold Limit Value established by ACGIH)
- 1344-28-1 Aluminum Oxide
- · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients are listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: Epoxy resin Aluminum Oxide **Boron Nitride** · Hazard statements Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause respiratory irritation. · Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves. Wear eye protection / face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center/doctor if you feel unwell. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 9)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 03/22/2024

Reviewed on 03/22/2024

Trade name: Medium Cure Ceramic Epoxy

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

· State Right to Know

All ingredients are listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

· Date of preparation / last revision 03/22/2024 / 2

· Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B Skin Sens. 1: Sensitization - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* Data compared to the previous version altered.