Visalia, CA 93277			
Product Information: 559-740-0912	8	303-739-1110	
Customer Service: 559-740-0912 Emergency Toll Free: 877-740-5015	1 5	Nevin House June 12, 2007	
Product Identification		,	
	Céramique High-Density Thermal Compou	nd	
Product Code: Céramique			
SECTION 2: COMPOSITION/INFORMATION ON IN	GREDIENTS		
Product Ingredient Information	CAS No.		
Aluminum Oxide Boron Nitride	1344-28-1 10043-11-5		
Zinc Oxide	1314-13-2		
Proprietary Oil Blend	Non-hazardous		
SECTION 3: HAZARD IDENTIFICATION			
Emergency Overview: Off white grease with slight odor. 7 Potential Health Effects:		tate eyes.	
Eyes: This product is an eye and mucus membrane irrit Skin: Not expected to be a skin irritant. Repeated and		irritation	
<u>Ingestion:</u> No adverse effects expected.	restonged skin contact courd cause minor skin		
Inhalation: No specific information available.			
Pre-Existing Medical Conditions Aggravated by Exposure:	Eye		
SECTION 4: FIRST AID MEASURES	fter initial fluching, remove any contact lange	and continue fluching	for at least 15 minutes. Here are
<u>Eyes:</u> Immediately flush with large amounts of water. A examined by a Physician.	ther initial nushing, remove any contact lense	es and continue mushing	for at least 15 minutes. Have eye
Skin: Remove contaminated clothing and wash skin with so	ap and water. Get medical attention if irritatio	n develops/persists. Wash	n clothes separately before reuse.
Ingestion: If appreciable quantities are swallowed, seek me			
Inhalation: Not likely route of exposure. If inhaled and irri	tation occurs, remove to fresh air. If irritation	persists, call a Physician.	
SECTION 5: FIRE FIGHTING MEASURES			
Flash Point: > 600°F (Setaflash) LEL/UEL: NA Extinguishing Media: Use carbon dioxide or dry chemicals	(% by volume in air) for small fires, aqueous foam or water for large	a fires involving this mate	rial
Fire Fighting Instructions: Remove all ignition sources. C			
safe distance. As in any fire, wear self-contained breathing a		1 1	e
SECTION 6: ACCIDENTAL RELEASE MEASURES		* * ·	* *
SPALLINDIN DE AVALIDEDITAL KELEASE WEASUKES -			
	n flames, etc.). Wear self-contained breathin	ng apparatus and appropr	iate personal protective equipment
<u>Large Spills:</u> Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent	material. Collect spill by scooping up liquid	s and absorbent material a	ind place in a sealed metal contained
<u>Large Spills:</u> Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead	s and absorbent material a to waterways and ground.	ind place in a sealed metal contained
<u>Large Spills:</u> Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material <u>Small Spills:</u> Absorb spill with absorbent material, then place	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead	s and absorbent material a to waterways and ground.	ind place in a sealed metal contained
<u>Large Spills:</u> Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material <u>Small Spills:</u> Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead te in a sealed metal container for proper dispos	s and absorbent material a to waterways and ground. al.	and place in a sealed metal contained
<u>Large Spills:</u> Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material <u>Small Spills:</u> Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosion	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu	s and absorbent material a to waterways and ground. al. ust be kept closed and ve	and place in a sealed metal contained
<u>Large Spills:</u> Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material <u>Small Spills:</u> Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosion concentration build-up. Store in a cool dry place. Do not	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw	and place in a sealed metal contained entilation provided to prevent vape ay from heat or sources of ignitio
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosion concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with	and place in a sealed metal container entilation provided to prevent vap- ay from heat or sources of ignitio h skin. Ensure that all equipment
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this ma data sheet must be observed for empty containers.	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with	and place in a sealed metal container entilation provided to prevent vape ay from heat or sources of ignition h skin. Ensure that all equipment
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN.	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing tterial may be hazardous when emptied due to	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with	and place in a sealed metal container entilation provided to prevent vap- ay from heat or sources of ignitio h skin. Ensure that all equipment
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing tterial may be hazardous when emptied due to	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with	and place in a sealed metal container entilation provided to prevent vap- ay from heat or sources of ignitio h skin. Ensure that all equipment
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines:	a material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing aterial may be hazardous when emptied due to ROTECTION	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue.	and place in a sealed metal containent entilation provided to prevent vap- ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosic concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME	material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing tterial may be hazardous when emptied due to	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with	and place in a sealed metal container entilation provided to prevent vap- ay from heat or sources of ignitio h skin. Ensure that all equipment
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this material data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PL Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride	e material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing aterial may be hazardous when emptied due to ROTECTION ACGIH TLV	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL	and place in a sealed metal containent entilation provided to prevent vap- ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosing concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide	e material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing aterial may be hazardous when emptied due to ROTECTION ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust)	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust)	and place in a sealed metal container entilation provided to prevent vap- ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosing concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide	e material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing aterial may be hazardous when emptied due to ROTECTION ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust)	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust)	and place in a sealed metal container entilation provided to prevent vap- ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PL Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes:	e material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing aterial may be hazardous when emptied due to ROTECTION ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust)	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust)	and place in a sealed metal container entilation provided to prevent vape ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosic concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health	Example: material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead to in a sealed metal container for proper disposed on proof electrical equipment. Containers must breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust) NA NFPA 0	s and absorbent material a to waterways and ground. al. ust be kept closed and ven n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0	and place in a sealed metal container entilation provided to prevent vape ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosic concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health Flammability	Example 1 in a sealed metal container for proper disposed in section above. Avoid prolonged breathing iterial may be hazardous when emptied due to a sealed metal constrainer in the section above. Avoid prolonged breathing iterial may be hazardous when emptied due to a section above. A comparison of the section above. A comparison of the section above. A comparison of the section above. Avoid prolonged breathing iterial may be hazardous when emptied due to a section above. A comparison of the se	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0 1	and place in a sealed metal container entilation provided to prevent vape ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix <u>NFPA and HMIS Codes:</u> Health Flammability Reactivity	Example: material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead to in a sealed metal container for proper disposed on proof electrical equipment. Containers must breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust) NA NFPA 0	s and absorbent material a to waterways and ground. al. ust be kept closed and ven n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0	and place in a sealed metal container entilation provided to prevent vape ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosic concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health	Example: material. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper disposed on proof electrical equipment. Containers must breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing the trial may be hazardous when emptied due to a section above. Avoid prolonged breathing the trial may be hazardous when emptied due to the trial may be hazardous when emptied due to a section above. A comparison of the due to the trial may be hazardous when emptied due to the trial may be haz	s and absorbent material a to waterways and ground. al. ust be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0 1 0 B	and place in a sealed metal container entilation provided to prevent vape ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health Flammability Reactivity Personal Protection SECTION 9: PHYSICAL AND CHEMICAL PROPERT Physical State: Off-White Grease	rematerial. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mus breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing iterial may be hazardous when emptied due to ROTECTION ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust) NA NFPA 0 1 0 1 0 1 0	s and absorbent material a to waterways and ground. al. ast be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0 1 0 B	and place in a sealed metal container entilation provided to prevent vap- ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health Flammability Reactivity Personal Protection SECTION 9: PHYSICAL AND CHEMICAL PROPERT Physical State: Off-White Grease Odor: Slight Odor	rematerial. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers must breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing terial may be hazardous when emptied due to ROTECTION ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust) NA NFPA 0 1 0 -	s and absorbent material a to waterways and ground. al. ast be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0 1 0 B billity in Water: <2.0% fic Gravity: 2.7-2.8	and place in a sealed metal contain entilation provided to prevent vap- ay from heat or sources of ignitio h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health Flammability Reactivity Personal Protection SECTION 9: PHYSICAL AND CHEMICAL PROPERT Physical State: Off-White Grease Odor: Slight Odor pH: NA	rematerial. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers mu breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing terial may be hazardous when emptied due to ROTECTION ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust) NA NFPA 0 1 0 - IES	s and absorbent material a to waterways and ground. al. ast be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0 1 0 B bility in Water: <2.0% fic Gravity: 2.7-2.8 oration Rate: slower	and place in a sealed metal contain entilation provided to prevent vap- ay from heat or sources of ignitio h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health Flammability Reactivity Personal Protection SECTION 9: PHYSICAL AND CHEMICAL PROPERT Physical State: Off-White Grease Odor: Slight Odor	rematerial. Collect spill by scooping up liquid from entering storm sewers, ditches that lead the in a sealed metal container for proper dispose on proof electrical equipment. Containers must breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing iterial may be hazardous when emptied due to ROTECTION ACGIH TLV 10 mg/m3 (dust) 10 mg/m3 (dust) 10 mg/m3 (dust) NA NFPA 0 1 0 - IES Solut Speci Evap (Buty	s and absorbent material a to waterways and ground. al. ast be kept closed and ve n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0 1 0 B billity in Water: <2.0% fic Gravity: 2.7-2.8	and place in a sealed metal contain entilation provided to prevent vap- ay from heat or sources of ignitio h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3
Large Spills: Remove all sources of ignition (sparks, ope Ventilate area and contain spill with sand or other absorbent for proper disposal. Do not flush to sewer. Prevent material Small Spills: Absorb spill with absorbent material, then place SECTION 7: HANDLING AND STORAGE Overheating may cause container to rupture. Use explosite concentration build-up. Store in a cool dry place. Do not Check all containers for leaks. Wear protective clothing as grounded to prevent static discharge. Containers of this mat data sheet must be observed for empty containers. KEEP OUT OF REACH OF CHILDREN. SECTION 8: EXPOSURE CONTROLS/PERSONAL PI Exposure Guidelines: CHEMICAL NAME Aluminum Oxide Boron Nitride Zinc Oxide Proprietary Oil Mix NFPA and HMIS Codes: Health Flammability Reactivity Personal Protection SECTION 9: PHYSICAL AND CHEMICAL PROPERT Physical State: Off-White Grease Odor: Slight Odor pH: NA Vapor Pressure: NA	Ematerial. Collect spill by scooping up liquid from entering storm sewers, ditches that lead te in a sealed metal container for proper disposed on proof electrical equipment. Containers must breathe vapor or get liquid in eyes, or on ski in section above. Avoid prolonged breathing terial may be hazardous when emptied due to a sealed metal constrainer and the section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial may be hazardous when emptied due to a section above. Avoid prolonged breathing terial due to a section above. Avoid prolonged breathing terial due to a section above. Avoid prolonged breathing terial due to a section above. Avoid prolonged breathing terial due to a section above. Avoid prolonged breathing terial due to a section above. Avoid prolonged breathing terial due to a section above. Avoid prolonged brea	s and absorbent material a to waterways and ground. al. ast be kept closed and ven n and clothing. Keep aw g of vapors or contact with o solid or vapor residue. OSHA PEL 10 mg/m3 (dust) 10 mg/m3 (dust) 15 mg/m3 (dust) NA HMIS 0 1 0 B bility in Water: <2.0% fic Gravity: 2.7-2.8 oration Rate: slower d acetate=1)	and place in a sealed metal container entilation provided to prevent vape ay from heat or sources of ignition h skin. Ensure that all equipment All hazard precautions given in th ACGIH STEL NA NA 10 mg/m3

SECTION 10: STABILITY AND REACTIVITY INFORMATION

Stability: This product is stable.

Conditions to Avoid: Contamination with incompatible materials.

Incompatibility: Avoid strong oxidizing agents, strong acids and alkalis.

Products of Decomposition: Carbon monoxide, carbon dioxide, silicon dioxide, oxides of nitrogen, and incompletely burned hydrocarbons which may include minute traces of formaldehyde. Reacts with acids and alkalis to form combustible hydrogen gas.

Hazardous Polymerization: May not occur.

Conditions to avoid: NA

SECTION 11: CARCINOGEN INFORMATION

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC

SECTION 12: ECOLOGICAL INFORMATION

Environmental Impact Information

Avoid runoff into storm sewers and ditches that lead to waterways. Water runoff can cause environmental damage.

REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is: 1-800-424-8802

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

SECTION 14: TRANSPORTATION INFORMATION

Air and Ground Shipments:

Not Regulated

SECTION 15: REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To- Know Act of 1986 (40 CFR 372).

Product contains no Section 313 listed chemicals.

This information should be included on all MSDSs copied and distributed for this material. <u>TOXIC SUBSTANCES CONTROL ACT (TSCA).</u> All ingredients of this product are listed on the TSCA Inventory.

SECTION 16: OTHER INFORMATION

Do not puncture or incinerate containers. Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

WHMIS: Ingredient disclosure list: None

Status: Noncontrolled

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.